## **GLASS FIBER**

DATA SHEET

# Chopped Strands CS 7938



Polymer	Phenolic			
	CS 7938 <sup>*</sup> is used for reinforcement of phenolic resin.			
Product Description	Good wettability and dispersibility			
	High mechanical strength			
Technical	Fiber Diameter (nom.)	11 µm		
Characteristics	Av. Fiber Length (nom.)	3 mm		
	Glass	E-Glass (DIN 1259)		
	Size	Polymeric size containing silane		
	Moisture content	≤ 0,05 wt%		
	Size content	approx. 0,75 wt%		
	(Original data ex works)			
Packaging	Big Bag, Octabin, PE Bags (see detailed information on next page)			
Storage	The glass fiber should be stored in a dry place, preferably at room tempera- ture and 50 - 70 % relative humidity.			
Contact	For further information please contact:			
	Mail	glassfiber@lanxess.com		
	Phone	+49 (0)700 glassfiber		
		+49 (0)700 45277342		

### GLASS FIBER

### DATA SHEET



# Packaging Information CS 7938

Big Bag, recyclable		Octabin		
Net Weight	800 kg	Net Weight	500 kg	
Dimensions Bag	870 x 870 x 1400 mm	Dimensions Octabin.	1086 x 1086 x 870 mm	
<b>Dimensions Pallet</b>	1000 x 1200 mm (CP1)	Dimensions Pallet	1140 x 1140 mm (CP9)	
Packaging Code	BC00 – FA080P	Packaging Code	ZJ00 – OA045T	
Bottom unloading thro	ugh discharge spout			
LAIXES				
PE Bags				
Net Weight Bag	20 kg			
Net Weight Pallet	20 kg x 50 = 1000 kg			
<b>Dimensions Pallet</b>	1300 x 1100 mm (CP7)			
Packaging Code	SD 00 – BA 100E			
	10 layers per pallet			

#### Disclaimer

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

Values

Unless specified to the contrary, the values given have been established on standardized test. The figures should be regarded as guide values only and not as binding minimum values.

© = LANXESS Deutschland GmbH | HPM Business Unit | all rights reserved www.glassfiber.lanxess.com Page 2 of 2 | Edition 04.06.2014