## **GLASS FIBER**

DATA SHEET

# Chopped Strands CS 7968

LAN	XESS Energizing Chemistry

		- Andrews and a second s			
Polymer	<b>PBT, PET and others</b> CS 7968 <sup>*</sup> is used for reinforcement of a wide range of thermoplastic polyester grades like PBT, PET, PC, PC/ABS blends.				
Product Description	High mechanical strength High strand integrity High resistance to hydrolysis				
Technical	Fiber Diameter (nom.)	11 µm			
Characteristics	Av. Fiber Length (nom.)	4,5 mm			
	Glass	E-Glass (DIN 1259)			
	Size	Polymeric size containing silane			
	Moisture content	≤ 0,05 wt%			
	Size content	approx. 0,90 wt%			
Packaging	Big Bag, Octatainer, PE Bags (	Big Bag, Octatainer, PE Bags (see detailed information on next page)			
Storage	The glass fiber should be stored in a dry place, preferably at room tempera- ture and 50 - 70 % relative humidity.				
Contact	For further information please contact:				
	Mail	glassfiber@lanxess.com			
	Phone	+49 (0)700 glassfiber			
		+49 (0)700 45277342			

### GLASS FIBER

DATA SHEET



# Packaging Information CS 7968

Big Bag, recyclable		Telescope Octabin	
Net Weight	800 kg	Net Weight	1000 kg
<b>Dimensions Bag</b>	870 x 870 x 1400 mm	Dimensions Octabin	1086 x 1086 x 1550 mm
<b>Dimensions Pallet</b>	1000 x 1200 mm (CP1)	Dimensions Pallet	1100 x 1100 mm
Packaging Code	BC00 – FA080P	Packaging Code	ZR10 TELESCOPE
Bottom unloading through discharge spout		Pallet with hole	450 x 450 mm
LANXESS			
PE Bags			
Net Weight Bag	20 kg		
Net Weight Pallet	20 kg x 50 = 1000 kg		
Dimensions Pallet	1300 x 1100 mm (CP7)		
Packaging Code	SD 00 – BA 100E		
	10 layers per pallet		

#### Disclaimer

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

Values

Unless specified to the contrary, the values given have been established on standardized test. The figures should be regarded as guide values only and not as binding minimum values.

© = LANXESS Deutschland GmbH | HPM Business Unit | all rights reserved www.glassfiber.lanxess.com Page 2 of 2 | Edition 03.07.2013